

Oak Authentic Vivo

10138098 / YEGVVKFD Article number Oak Wood Grading Vivo Product type 3-layer parquet 14mm Plank Castle Format Dimensions 14 x 209 x 2200 mm Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Natural oil Appearance Golden floors Colour Authentic

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classification
Density

Product details / Technical properties

	Moisture content	5-9%
	Fire protection classification	Dfl-s1
	Content of formaldehyde	E 1
	PCP content	NPD
	Brinell Value	38
	Shrinking and swelling	
	Breaking strength	NPD
	Thermal conductivity	
	Thermal resistance value	
	Antislip performance (CE)	USRV 45
rces	Antislip performance (DIN)	R10
	Nobb.number	56477714
	EAN Code	7035580213147





beveled 2V

brushed

2,76

21.5

138

50

1075 EN 13489

Class 1

controlled sour

>= 500kg/m³

6

1







Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

